



Prestige

Prestige not only offers a finely textured and durable surface with a brighter 'blue-white' colour and high light reflectance, it also offers a balance of both sound absorption and sound attenuation. Providing the perfect balance between open spaces or personal office.

Key Features

- // Good sound absorption: up to 0.70 α_w
- // Very high light reflectance: 87%
- // Reinforced scratch resistant face
- // Better finish and more durable edges
- // ISO 4 / A+
- // 30 year system guarantee
- // Ideal for meeting rooms or waiting areas
- // SL2 Planks: Ideal for both open areas and corridors



Edge Detail	Board	Tegular24	Tegular15	Integra	Conceal	SL2
Thickness (mm)	19	19	19	19	19	19
Modules (mm)	600 x 600 ..7661M 1200 x 600 ..7663M	600 x 600 ..7664M 1200 x 600 ..7666M	600 x 600 ..7674M 1200 x 300 ..7676M 1200 x 600 ..7677M	600 x 600 ..7681M	600 x 600 ..7715M 1200 x 600 ..7716M	1500 x 300 ..7699M* 1800 x 3007701*
Suspension Systems	Gridline 24 Butt Cut / Joggled	Gridline 24 Butt Cut / Joggled	Gridline 15 Butt Cut / Joggled Interlude HRC Silhouette	Gridline 24 Butt Cut / Joggled	Gridline System Z – L-Bar	Gridline System Z – T-Bar Gridline System Z – Z-Bar

Colour Global White

Sustainability



41-80



A+¹



EN 13964 / E1

¹Except Integra: A

Acoustics



EN ISO 354
& EN ISO 11654



EN ISO 10848-2
& EN ISO 717-1



EN ISO 140-3
& EN ISO 717-1

Results based on Global White tiles

	Hz α_p										
	α_w	D_{nfw}	R_w	Class	NRC	125	250	500	1000	2000	4000
Board, Tegular24, Tegular15	0.70(H)	37 dB	20 dB	C	0.70	0.45	0.50	0.60	0.80	0.85	0.95
Integra	0.70(H)	-	-	C	0.65	0.40	0.50	0.60	0.70	0.75	0.90
Conceal	0.70(H)	-	-	C	0.75	0.40	0.50	0.65	0.85	0.95	1.00
SL2	0.65(H)	40 dB	-	C	0.65	0.35	0.45	0.55	0.75	0.90	1.00

Fire Reaction



A2-s1, d0
EN 13501-1

Performances & Features



87%



ISO 4
($\geq 0,5\mu m$)
ISO 14644-1:
2015



CP_(0.5)⁵
NFS 90-351



30 Year
System
Guarantee



95% RH



5.0 Kg/m²
Board, Tegular24,
Tegular15,
Conceal, SL2
5.8 Kg/m² Integra



BIM
READY

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 156.7.06.24