




Oplia hA

Oplia hA is a smooth laminated finish and Class A sound absorption, making it ideal for open plan areas.

Key Features

- Excellent sound absorption: up to 0.95 α_w
- Better finish and more durable edges
- Available with SL2 edge detail
- Ideal for open spaces, call centres, libraries and schools



Edge Detail	Board	Tegular24	Tegular15	SL2
Thickness (mm)	15 / 19	15	15	19
Modules (mm)	600 x 600 x 15... 3819M 1200 x 600 x 15... 3821M 1500 x 600 x 19... 3092M 1800 x 600 x 19... 3093M	600 x 600 x 15... 5173M 1200 x 600 x 15... 5177M	600 x 600 x 15... 5174M 1200 x 600 x 15... 5178M	1500 x 300... 3094M 1800 x 300... 3096M
Suspension Systems	Gridline 24 Butt Cut / Joggled	Gridline 24 Butt Cut / Joggled	Gridline 15 Butt Cut / Joggled Interlude HRC Silhouette	Gridline System Z – T-Bar Gridline System Z – Z-Bar
Colour	Global White			
Sustainability	44% A+ EN 13964 / E1			

Acoustics

Results based on Global White tiles

				Hz α_p							
	α_w	D_{nfw}	R_w	Class	NRC	125	250	500	1000	2000	4000
Board, Tegular24, Tegular15 (15mm)	0.95	–	–	A	0.90	0.60	0.80	0.95	0.90	1.00	1.00
Board (19mm)	0.95	25 dB	10 dB	A	0.90	0.50	0.85	0.95	0.90	1.00	1.00
SL2	0.95	27 dB	–	A	0.90	0.45	0.85	0.95	0.90	0.95	1.00

Fire Reaction



Euroclass A2-s1, d0
EN 13501-1

Performances & Features



85%



ISO 5



¹Except 5177M & 5178M (70% RH)



95% RH¹



2.4 Kg/m² (15mm)
2.9 Kg/m² (19mm)
3.3 Kg/m² (Planks)



If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 169.6.04.24