




## Oplia hA dB

Oplia hA dB combines the smooth Oplia laminated appearance with the highest levels of sound absorption and sound attenuation in one tile, providing a solution for flexible working spaces.

## Key Features

- Opia hA dB includes a large selection of sizes and quality edge details enhancing durability
- The best acoustical combination of high sound absorption and high sound attenuation properties
- Ideal for open plan offices, board rooms, SEN schools and libraries



Edge Detail	Board		Tegular24		Tegular15																	
Thickness (mm)	40		40		40																	
Modules (mm)	600 x 600 ..... 5044M 1200 x 600 ..... 5045M		600 x 600 ..... 5104M		600 x 600 ..... 5114M																	
Suspension Systems	Gridline 24 Butt Cut / Joggled		Gridline 24 Butt Cut / Joggled		Gridline 15 Butt Cut / Joggled Silhouette																	
Sustainability	 44		 A+	 EN 13964 / E1																		
Colour	Global white																					
Acoustics	<div><div> EN ISO 354 &amp; EN ISO 11654 <math>\alpha_w</math></div><div> EN ISO 10848-2 &amp; EN ISO 717-1 D<sub>nfw</sub></div><div> EN ISO 140-3 &amp; EN ISO 717-1 R<sub>w</sub></div><div><table><tr><th>Class</th><th>NRC</th><th>125</th><th>250</th><th>500</th><th>1000</th><th>2000</th><th>4000</th></tr><tr><td>A</td><td>0.85</td><td>0.35</td><td>0.60</td><td>0.90</td><td>1.00</td><td>1.00</td><td>1.00</td></tr></table></div></div> <div>Board, Tegular24, Tegular15</div>						Class	NRC	125	250	500	1000	2000	4000	A	0.85	0.35	0.60	0.90	1.00	1.00	1.00
Class	NRC	125	250	500	1000	2000	4000															
A	0.85	0.35	0.60	0.90	1.00	1.00	1.00															
Fire Reaction	<div> Euroclass A2-s1, d0 EN 13501-1</div>																					
Performances & Features	<div> 85%</div>	<div> 95% RH</div>	<div> ISO 5 ISO 14644-1</div>	<div></div>	<div>30 Year System Guarantee</div>	<div>BIM READY</div>																
	<div> 6.2 Kg/m<sup>2</sup></div>	<div></div>	<div></div>	<div></div>																		

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email [enquiries@zentia.com](mailto:enquiries@zentia.com)

TDS 172.3.12.24