




Oplia hA+

Oplia hA+ is a smooth laminated finish and offers the highest level of sound absorption ($1.00 \alpha_w$), making it ideal for open plan spaces.

Key Features

- Excellent sound absorption: $1.00 \alpha_w$
- High light reflectance: 85%
- Better finish and more durable edges
- Ideal for open spaces, call centres, open plan offices and SEN schools



Edge Detail	Board	Tegular24	Tegular15
Thickness (mm)	20	20	20
Modules (mm)	600 x 600 3861M 1200 x 600 3863M	600 x 600 3866M	600 x 600 2097M
Suspension Systems	Gridline 24 Butt Cut / Joggled Prelude 24 Sixty ²	Gridline 24 Butt Cut / Joggled Prelude 24 Sixty ²	Gridline 15 Butt Cut / Joggled Interlude HRC Silhouette
Colour	Global White		

Sustainability



44



A+



EN 13964 / E1



Acoustics



EN ISO 354
& EN ISO 11654



EN ISO 10848-2
& EN ISO 717-1



EN ISO 140-3
& EN ISO 717-1

Results based on Global White tiles

	α_w	D _{nfw}	R _w	Class	NRC	Hz α_p					
						125	250	500	1000	2000	4000
Board, Tegular24, Tegular15	1.00	33 dB	15 dB	A	0.95	0.65	0.80	0.95	0.95	1.00	1.00

Fire Reaction



Euroclass A2-s1, d0
EN 13501-1

Performances & Features



85%



95% RH



30 Year
System
Guarantee



3.1 Kg/m²



ISO 5



ISO 14644-1



BIM
READY

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 170.4.04.24