


## **Key Features**

- Excellent sound attenuation (39 dB sound reduction) to eliminate the need for sound barriers in close office applications
- Enhanced acoustical absorption performance of 0.60 Q<sub>w</sub> for better acoustic comfort
- Fully painted, reinforced edges for a more robust tile and greater durability
- // Improved aesthetics with discreet perforations, a smoother finish and a classleading, fully painted whiteness
- Easy to handle and re-engineered for a better, easier fit
- Ideal for individual offices and board rooms



Edge Detail	Board	Tegular24	Tegular15				
	<u> </u>	© 24					
Thickness (mm)	19	19	19				
Modules (mm)	600 x 600 5477M	600 x 600 5479M	600 x 600 5481N				
Suspension Systems	Gridline 24 Butt Cut / Joggled	Gridline 24 Butt Cut / Joggled	Gridline 15 Butt Cut Gridline 15 Shadow				
Colour	Global White						
Sustainability			RAIR COMES				
Acoustics	37	A+ EN 13964 / E1					

Acoustics



	$\alpha_{\sf w}$	$D_{nfw}$	R <sub>w</sub>	Class	NRC	125	250	500	1000	2000	4000
Board, Tegular24, Tegular15	0.60	39 dB	20 dB	С	0.55	0.35	0.40	0.60	0.65	0.75	0.65

**Fire Reaction** 



Euroclass A2-s1, d0 EN 13501-1

Performances & Features



85%



95% RH







Hz α<sub>P</sub>





7.9 Kg/m²







If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on 0800 371 849 or email enquiries@zentia.com

TDS 135.3.03.25

