




## Aruba hH (High Humidity)


Aruba hH (High Humidity) is a tough and reliable humidity resistant ceiling tile. Stable at up to 99% Relative Humidity (RH), it is ideal for high humidity areas such as changing rooms.

## Key Features

- Up to 99% RH
- Available in Board edge
- Offers Class C sound absorption and good attenuation for excellent acoustic performance
- Available in Global White, giving warm and damp spaces a brighter and cooler appearance
- Ideal for high humidity areas such as changing rooms
- Excellent technical performance in humid conditions when used alongside Gridline 24 Corrosive Resistant suspended ceiling grid



Edge Detail	Board
-------------	-------



<b>Thickness (mm)</b>	15
-----------------------	----

<b>Modules (mm)</b>	600 x 600 ..... 5499M
---------------------	-----------------------

<b>Suspension Systems</b>	Gridline 24 Butt Cut / Joggled Gridline 24 Corrosive Resistant
---------------------------	---

<b>Colour</b>	Global White
---------------	--------------

**Sustainability**

44

A

EN 13964 / E1

**Acoustics**

EN ISO 354 & EN ISO 11654

EN ISO 10848-2 & EN ISO 717-1

	Hz $\alpha_p$									
	$\alpha_w$	$D_{nfw}$	Class	NRC	125	250	500	1000	2000	4000
Board	0.60	34 dB	C	0.55	0.35	0.45	0.60	0.60	0.60	0.60

**Fire Reaction**

Euroclass A2-s1, d0  
EN 13501-1

**Performances & Features**

85%

99% RH

Lifetime Guarantee

30 Year System Guarantee

3.6 Kg/m<sup>2</sup>

BIM READY

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email [enquiries@zentia.com](mailto:enquiries@zentia.com)

TDS 138.5.03.25