



## Biobloc Plain

Biobloc Plain combines excellent cleanability and resistance to disinfectants. Along with its antimicrobial performance it is an ideal solution for healthcare environments.

## Key Features

- // Available in Plain surface with enhanced water repellency
- // High light reflectance: 87%
- // Washable
- // Safe use with disinfectants
- // ISO 5
- // Ideal for healthcare environments with average to severe risk of infection

Biobloc Plain complies with the NF S 90-351 (2013) microbiological classification M1 and the most onerous risk Zone 4. The  $\leq 1$  colony forming unit per  $m^3$  air M1 results were achieved in tests with:

- // Methicillin Resistant Staphylococcus Aureus (MRSA)
- // Escherichia coli (E-coli)
- // Bacillus cereus
- // Acinetobacter baumannii
- // Klebsiella pneumoniae
- // Streptococcus pneumoniae
- // Candida albicans
- //  $<1$  was achieved for Aspergillus brasiliensis (Fungus) tests

Edge Detail	Board	Tegular24	Tegular15
Thickness (mm)	15	15	15
Modules (mm)	600 x 600 ..... 2221M 1200 x 600 ..... 2222M	600 x 600 ..... 2223M	600 x 600 ..... 2224M
Suspension Systems	Gridline 24 Butt Cut / Joggled Gridline 24 Corrosive Resistant Gridline 24 Clean	Gridline 24 Butt Cut / Joggled Gridline 24 Clean	Gridline 15 Butt Cut / Joggled
Colour	Global White		

## Sustainability



31



A+



EN 13964 / E1

## Acoustics



EN ISO 354  
& EN ISO 11654



EN ISO 10848-2  
& EN ISO 717-1



EN ISO 140-3  
& EN ISO 717-1

	Hz $\alpha_p$										
	$\alpha_w$	$D_{nfw}$	$R_w$	Class	NRC	125	250	500	1000	2000	4000
Board, Tegular24, Tegular15	0.20(L)	35 dB	19 dB	E	0.20	0.40	0.25	0.15	0.15	0.20	0.30

## Fire Reaction



Euroclass A2-s1, d0  
EN 13501-1

## Performances & Features



87%



95% RH



ISO 5



3.6 Kg/m<sup>2</sup>



If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email [enquiries@zentia.com](mailto:enquiries@zentia.com)

TDS 162.4.03.25