






## Oplia dB

Oplia dB is a smooth laminated finish providing enhanced sound attenuation performance for improving the privacy between adjacent spaces.

## Key Features

- Excellent level of sound attenuation: up to 41 dB
- High light reflectance: 86%
- Better finish and more durable edges
- ISO 5 / A+
- Ideal for individual offices

| Edge Detail        | Board   | Tegular24   | Tegular15   |
|--------------------|---|---|---|
|                    |  |  |  |
| Thickness (mm)     | 19  | 19  | 19  |
| Modules (mm)       | 600 x 600 .....3191M  | 600 x 600 .....3192M  | 600 x 600 .....2095M  |
| Suspension Systems | Gridline 24 Butt Cut / Joggled  | Gridline 24 Butt Cut / Joggled  | Gridline 15 Butt Cut / Joggled<br>Gridline 15 Shadow                                |

## Sustainability



39



A+



EN 13964 / E1



## Colour

Global white

## Acoustics



EN ISO 354  
& EN ISO 11654



EN ISO 10848-2  
& EN ISO 717-1



EN ISO 140-3  
& EN ISO 717-1

Hz  $\alpha_p$

|                             | $\alpha_w$ | $D_{nfw}$ | $R_w$ | Class | NRC  | 125  | 250  | 500  | 1000 | 2000 | 4000 |
|-----------------------------|------------|-----------|-------|-------|------|------|------|------|------|------|------|
| Board, Tegular24, Tegular15 | 0.60(H)    | 41 dB     | 21 dB | C     | 0.65 | 0.30 | 0.40 | 0.55 | 0.70 | 0.85 | 0.95 |

## Fire Reaction



Euroclass A2-s1, d0  
EN 13501-1

## Performances & Features



86%



95% RH



30 Year  
System  
Guarantee



7.6 Kg/m<sup>2</sup>



ISO 5



ISO 14644-1



BIM  
READY

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email [enquiries@zentia.com](mailto:enquiries@zentia.com)

TDS 171.5.03.25