


## Oplia hA dB

Oplia hA dB combines the smooth Oplia laminated appearance with the highest levels of sound absorption and sound attenuation in one tile, providing a solution for flexible working spaces.

## Key Features

- Opelia hA dB includes a large selection of sizes and quality edge details enhancing durability
- The best acoustical combination of high sound absorption and high sound attenuation properties
- Ideal for open plan offices, board rooms, SEN schools and libraries



Edge Detail	Board	Tegular24	Tegular15
<b>Thickness (mm)</b>	40	40	40
<b>Modules (mm)</b>	600 x 600 ..... 5044M 1200 x 600 ..... 5045M	600 x 600 ..... 5104M	600 x 600 ..... 5114M
<b>Suspension Systems</b>	Gridline 24 Butt Cut / Joggled	Gridline 24 Butt Cut / Joggled	Gridline 15 Butt Cut / Joggled Gridline 24 Shadow

### Sustainability



44



A+



EN 13964 / E1

### Colour

Global white

### Acoustics



EN ISO 354 & EN ISO 11654



EN ISO 10848-2 & EN ISO 717-1



EN ISO 140-3 & EN ISO 717-1

Hz  $\alpha_p$

	$\alpha_w$	Dnfw	R <sub>w</sub>	Class	NRC	125	250	500	1000	2000	4000
Board, Tegular24, Tegular15	0.90	40 dB	20 dB	A	0.85	0.35	0.60	0.90	1.00	1.00	1.00

### Fire Reaction



Euroclass A2-s1, d0  
EN 13501-1

### Performances & Features



85%



95% RH



ISO 5

ISO 14644-1



30 Year System Guarantee



6.2 Kg/m<sup>2</sup>



BIM READY

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email [enquiries@zentia.com](mailto:enquiries@zentia.com)

TDS 172.5.03.25