




Oplia hA

Oplia hA is a smooth laminated finish and Class A sound absorption, making it ideal for open plan areas.

Key Features

- Excellent sound absorption: up to 0.95 α_w
- Better finish and more durable edges
- Ideal for open spaces, call centres, libraries and schools



Edge Detail	Board	Tegular24	Tegular15
Thickness (mm)	15	15	15
Modules (mm)	600 x 600 x 15..... 3819M 1200 x 600 x 15..... 3821M	600 x 600 x 15..... 5173M 1200 x 600 x 15..... 5177M	600 x 600 x 15..... 5174M 1200 x 600 x 15..... 5178M
Suspension Systems	Gridline 24 Butt Cut / Joggled	Gridline 24 Butt Cut / Joggled	Gridline 15 Butt Cut / Joggled Gridline 15 Shadow

Colour Global White

Sustainability



44



A+



EN 13964 / E1

Acoustics

Results based on Global White tiles



EN ISO 354
& EN ISO 11654



EN ISO 10848-2
& EN ISO 717-1



EN ISO 140-3
& EN ISO 717-1

	α_w	D_{nfw}	R_w	Class	NRC	Hz α_p					
						125	250	500	1000	2000	4000
Board, Tegular24, Tegular15 (15mm)	0.95	-	-	A	0.90	0.60	0.80	0.95	0.90	1.00	1.00

Fire Reaction



Euroclass A2-s1, d0
EN 13501-1

Performances & Features



85%



ISO 5



ISO 14644-1



30 Year
System
Guarantee

¹Except 5177M & 5178M (70% RH)



95% RH¹



2.4 Kg/m² (15mm)



BIM
READY

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 169.8.03.25