




Oplia

Oplia is a smooth laminated finish providing balanced acoustic performance combining both sound absorption and sound attenuation.

Key Features

- ✓ Winning balance of sound attenuation and absorption
- ✓ Enhanced product durability
- ✓ High light reflectance: 86%
- ✓ ISO 5 / A+
- ✓ Ideal for open plan offices, board rooms, SEN schools and libraries



Edge Detail	Board	Tegular24	Tegular15
Thickness (mm)	17	17	17
Modules (mm)	600 x 600 2801M 1200 x 600 2802M Triangle Tile 1200 x 1200 x 1200 . BPTT2802M	600 x 600 2803M	600 x 600 2805M
Suspension Systems	Gridline 24 Butt Cut / Joggled Prelude 24 Sixty ²	Gridline 24 Butt Cut / Joggled Prelude 24 Sixty ²	Gridline 15 Butt Cut/ Joggled Gridline 15 Shadow

Colour Global White

Sustainability



80



A+



EN 13964 / E1



Acoustics



EN ISO 354 & EN ISO 11654



EN ISO 10848-2 & EN ISO 717-1



EN ISO 140-3 & EN ISO 717-1

Results based on Global White tiles

	α_w	D _{nfw}	R _w	Class	NRC	Hz α_p						
						125	250	500	1000	2000	4000	
Board, Tegular24, Tegular15	0.65(H)	37 dB	20 dB	C	0.65	0.55	0.50	0.55	0.75	0.85	0.85	
Triangle	0.90	-	-	A	0.90	0.65	0.80	0.85	0.90	1.00	1.00	

Fire Reaction



Euroclass A2-s1, d0
EN 13501-1

Performances & Features



86%



95% RH



4.6 Kg/m²



ISO 5



ISO 14644-1



If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 168.5.03.25