



Prestige

Prestige not only offers a finely textured and durable surface with a brighter 'blue-white' colour and high light reflectance, it also offers a balance of both sound absorption and sound attenuation. Providing the perfect balance between open spaces or personal office.

Key Features

- Good sound absorption: up to 0.70 α_w
- Very high light reflectance: 87%
- Reinforced scratch resistant face
- Better finish and more durable edges
- ISO 4 / A+
- 30 year system guarantee
- Ideal for meeting rooms or waiting areas
- SL2 Planks: Ideal for both open areas and corridors



| Edge Detail | Board | Tegular24 | Tegular15 | Integra | Conceal | SL2 |
|---------------------------|-----------------------------------------|-----------------------------------------|---------------------------------------------------------------|--------------------------------|-----------------------------------------|--------------------------------------------------------|
| | | | | | | |
| Thickness (mm) | 19 | 19 | 19 | 19 | 19 | 19 |
| Modules (mm) | 600 x 600 ..7661M 1200 x 600 ..7663M | 600 x 600 ..7664M 1200 x 600 ..7666M | 600 x 600 ..7674M 1200 x 300 ..7676M 1200 x 600 ..7677M | 600 x 600 ..7681M | 600 x 600 ..7715M 1200 x 600 ..7716M | 1500 x 300 ..7699M* 1800 x 3007701* |
| Suspension Systems | Gridline 24 Butt Cut / Joggled | Gridline 24 Butt Cut / Joggled | Gridline 15 Butt Cut / Joggled Gridline 15 Shadow | Gridline 24 Butt Cut / Joggled | Gridline System Z – L-Bar | Gridline System Z – T-Bar Gridline System Z – Z-Bar |

Sustainability



41-80



A+¹



EN 13964 / E1

¹Except Integra: A

Acoustics



EN ISO 354
& EN ISO 11654



EN ISO 10848-2
& EN ISO 717-1



EN ISO 140-3
& EN ISO 717-1

Results based on Global White tiles

| | α_w | D_{nfw} | R_w | Class | NRC | Hz α_p | | | | | | |
|-----------------------------|------------|-----------|-------|-------|------|---------------|------|------|------|------|------|--|
| | | | | | | 125 | 250 | 500 | 1000 | 2000 | 4000 | |
| Board, Tegular24, Tegular15 | 0.70(H) | 37 dB | 20 dB | C | 0.70 | 0.45 | 0.50 | 0.60 | 0.80 | 0.85 | 0.95 | |
| Integra | 0.70(H) | - | - | C | 0.65 | 0.40 | 0.50 | 0.60 | 0.70 | 0.75 | 0.90 | |
| Conceal | 0.70(H) | - | - | C | 0.75 | 0.40 | 0.50 | 0.65 | 0.85 | 0.95 | 1.00 | |
| SL2 | 0.65(H) | 40 dB | - | C | 0.65 | 0.35 | 0.45 | 0.55 | 0.75 | 0.90 | 1.00 | |

Fire Reaction



A2-s1, d0
EN 13501-1

Performances & Features



87%



ISO 4
($\geq 0,5\mu m$)
ISO 14644-1:
2015



CP_(0,5)⁵
NFS90-351



30 Year
System
Guarantee



95% RH



5.0 Kg/m²
Board, Tegular24,
Tegular15,
Conceal, SL2,
Integra



BIM
READY

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 156.9.03.25