

Titan (100% RH)


With its unique high density mineral composition, Titan is steam resistant and will retain its physical integrity even when subjected to 100% RH. It also features a washable finish and is lightly fissured to provide acoustic performance.

Key Features

- 100% RH resistance
- Durable, washable and scrubbable
- Resistant to growth of mould, mildew and bacteria
- Good balance between sound attenuation and absorption
- Ideal for swimming pools, locker rooms, shower areas and indoor parking areas



Edge Detail Board



Thickness (mm)	15
Modules (mm)	600 x 600 607M
Suspension Systems	Gridline 24 Butt Cut / Jogged Gridline 24 Corrosive Resistant ¹ Gridline 24 Clean
Colour	Global White

¹Titan must be installed on Gridline 24 Corrosive Resistant grid where humidity regularly exceeds 95% RH. Titan may need to have Main Runners at 600 mm centres due to increased weight in high humidity conditions.

Sustainability	37		A+	EN 13964 / E1
-----------------------	----	--	----	---------------

Acoustics	EN ISO 354 & EN ISO 11654	EN ISO 10848-2 & EN ISO 717-1								
	α_w	D_{nfw}	Class	NRC	125	250	500	1000	2000	4000
Board	0.55(MH)	-	D	0.60	0.25	0.30	0.50	0.80	0.85	0.75

Fire Reaction	Euroclass A1 EN 13501-1
----------------------	----------------------------

Performances & Features	79%	7.3Kg/m ² 20 Kg/m ² > if wet			
	100% RH				

While this product is suitable for high humidity environments, it is not suitable to be fitted directly over a swimming pool.

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 234.1.02.25